



Labglassfiber

Product technical sheet

Characteristics: Raw fabric plot. Glassfiber covering with narrow plot.

Ideal use: This finishing is suitable for inner spaces and damp locations:

bathroom, shower, spa, so as for every location where hygiene is extremely important. It is also perfect as kitchen back bet ween bases and cabinets, or for medical locations, such as clinics and hospitals and for floors.

The wall: In order to be covered it must have a dry and well-shaven surface.

For all those cases where the wall is not smooth, as in the case of tiles, the surface will have to be properly plastered and shaved.

Cleaning: Request information sheet.

Technical features:

Classification	Non- homogeneous product			
Substrate	Gypsum board acc. To DIN EN 13238:2010-06 ³			
Application quantity	200 m ²			
Colour	Gray striped			
Area weight	225,6 g/m ² ±10 g/m ²			
Test metod	Parameter	number of tests	Results	
			mean	parameter
DIN EN 13823:2015-02	FIGRA 0,2MJ ≤120W/S	3	46,25	J
DIN EN 13823:2015-02	FIGRA 0,4MJ	3	4,60	-
DIN EN 13823:2015-02	THR 600S ≤7,5MJ	3	1,144	J
DIN EN 13823:2015-02	SMOGRA ≤ 180 m ² /s ²	3	24,50	J
DIN EN 13823:2015-02	TSP 600S ≤ 200 m ²	3	46,57	J
DIN EN 13823:2015-02	LFS < Border of the sample	3	yes	J
DIN EN 13823:2015-02	Flaming droplets/particles	3	no	J
DIN EN ISO 11925-2:2011-02		12	yes	J
Surface/ edge flame attack 30 s Exposure	Fs ≤ 150 mm			
Flaming droplets/particles	Ignition of filter paper	12	no	J
Classification of fire behaviorur B - s1, d0				

Warnings: This is a product for professional use. Follow national rules and regulations. Please check that the surface is perfectly clean, dry and planar. If necessary, please request the safety data sheet. For unexpected events please contact TapLab Assistance Service:
press@taplab.it