



Labjewel

Product technical sheet

Characteristics: Vinyl wall covering with heavy vinyl front side. Back side in non-woven fabric.

Ideal use: A solution to cover the walls of any kind of environment in residential or commercial areas. The finish of the product is a light texture that enhances the design and makes it tactile.

The wall: In order to be covered it must have a dry and well-shaven surface. For all those cases where the wall is not smooth, as in the case of tiles, the surface will have to be properly plastered and shaved.

Cleaning: Request information sheet.

Technical features:

weigh	240/480 gr./sm
heigth	50 cm.
fire rating	Euro class B-s2-d0 class Euro Classification EN 15102:2007+A1:2011 - par.4.1
Release of formaldehyde passed	EN 15102:2007+A1:2011 - par.4.2
High metals and specific elements	EN 15102:2007+A1:2011 - par.4.3.1 Barium (<5 mg/kg) Arsenic (<5 mg/kg) Antimony (<5 mg/kg) Cadmium (<5 mg/kg) Crome (<5 mg/kg) Lead (<5 mg/kg) Mercury (<5 mg/kg) Selenium (<5 mg/kg)
Release of Vinyl Monomer (VCM)	EN 15102:2007+A1:2011 - par.4.3.1
Sound Absorption	NDP EN 15102:2007+A1:2011 - par.4.4
Thermic Resistance	NDP EN 15102:2007+A1:2011 - par.4.5

Warnings: This is a product for professional use. Follow national rules and regulations. Please check that the surface is perfectly clean, dry and planar. If necessary, please request the safety data sheet. For unexpected events please contact TapLab Assistance Service: press@taplab.it